

## How to reset the AHM27292U

1. Use putty, if doesn't have putty, go to here to download <u>https://www.putty.org/</u>



1. Check Network Connections has "Remote NDNS Compatible Device" and in Device Manager check which COM port use for AHM27292U

🛃 Device Manager	Vetwork Connections		
File Action View Help	$\leftarrow$ $\rightarrow$ $\checkmark$ $\bigstar$ Network and Internet $\rightarrow$ Network		
	Organize 🔻 Connect To Disable this network dev		
DESKTOP-6V7J5JO			
Audio inputs and outputs	internet		
> 💻 Computer	Disconnected		
> 👝 Disk drives	Qualcomm USB Modem 6000		
> 🕞 Display adapters	VirtualBox Host-Only Network		
DVD/CD-ROM drives	Enabled		
> Firmware	VirtualBox Host-Only Ethernet Ad		
> Human Interface Devices	Wi-Fi 6		
> The AIA/AIAPI controllers	Not connected		
Keyboards	🗙 📶 Intel(R) Wi-Fi 6E AX210 160MHz		
Mice and other pointing devices	Wireless Terminal		
> Monitors	Disconnected		
Postable Davies	Qualcomm USB Modem 6000		
Portable Devices			
▼ ■ Ports (COM & LPT) ■ USP 应利装罢 (COM4)	Network cable unplugged		
■ 05B 序列表直 (COM4)	🗙 🐗 Realtek PCIe GBE Family Controller		
	▲ □ □ 乙太網路 14		
Software devices	Network cable unplugged		
Sound video and game controllers	X Marvell AQtion 10Gbit Network A		
Storage controllers	□ 乙太網路3		
System devices	無法辨識的網路		
Universal Serial Bus controllers	Remote NDIS Compatible Device		



 $\geq$ 

2. Open Putty and choose Serial, In Serial Line bar type-in which COM port show in your device manager (in this sample, my computer shows COM4) and speed type-in 115200

🕵 PuTTY Configuration		? ×	
Category:			
Category: Session Logging Terminal Keyboard Bell Features Window Appearance Behaviour Translation Colours Colours Connection Data Proxy Telnet Rlogin SSH Serial	Basic options for your PuTTY session         Specify the destination you want to connect to         Serial line       Speed         COM4       115200         Connection type:       Raw         Raw       Telnet       Rlogin         Load, save or delete a stored session		
	Saved Sessions Default Settings	Load Save Delete	
	Close window on exit: Always Never Only on clean exit		
About Help	Open	Cancel	

> Double hit "Enther" from keyboard to enter

Putty	_	$\times$
Please press Enter to activate this console.		^
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
   _   _                 _     _   _   _                _         W I R E L E S S F R E E D O M		
OpenWrt SNAPSHOT, r17031+232-e6b3e77e6e		
=== WARNING! ====================================		
root@HaLow_STA:/# root@HaLow_STA:/# []		~



Type in "firstboot && reboot now" then hit "Enter" and it will show "This will erase all settings and remove any installed packages. Are you sure? [N/y], then hit "y" from keyboard and hit "Enter" to start to reset to factory default, it will take few minutes.

After reboot, you can check Network Connections "Remote NDNS Compatible Device" and will auto assigned IP from 192.168.1.x range

Putty	_	×
Please press Enter to activate this console.		$\sim$
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
_		
Openwrt SNAPSHOT, r1/031+232-060307/060		
=== WARNING! ====================================		
There is no root password defined on this device! Use the "passwd" command to set up a new password		
in order to prevent unauthorized SSH logins.		
root@HaLow_STA:/# firstboot && reboot now_		
		~
Putty	_	×
		^
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		
BusyBox v1.33.1 (2021-07-31 16:57:34 UTC) built-in shell (ash)		

root@HaLow\_STA:/# firstboot && reboot now This will erase all settings and remove any installed packages. Are you sure? [N /y]